

Neural-network-backed evolutionary search for SrTiO_3 surface reconstructions


Ralf Wanzenböck, Jesús Carrete, Marco Arrigoni, Georg K. H. Madsen

2021-11-17

Institute of Materials Chemistry, TU Wien



TACO
TAMING COMPLEXITY
TOGETHER



Introduction


Goal:

Global structure exploration of SrTiO_3 surfaces by combining

- evolutionary search strategies and
- machine learning techniques.




Wikimedia Commons.




David Ha, blog.otoro.net (2017).

Strontium titanate

- Cubic perovskite oxide
- n-type semiconductor
- *very practical* material



Riva et al., Phys. Rev. Mater. 3, 043802 (2019).




Enterkin. Nat. Mater. 9 (2010).

Objectives

Adapt CMA-ES to surface structures

- Redefine parameters in contrast to bulk systems.
- Compatibility with GPAW (parallelization, call structure).




Objectives

Adapt CMA-ES to surface structures

- Redefine parameters in contrast to bulk systems.
- Compatibility with GPAW (parallelization, call structure).

Train a surrogate neural-network model

- Generate data (training, validation, test).
- Adapt the NN parameters and loss function.



Objectives

Adapt CMA-ES to surface structures


- Redefine parameters in contrast to bulk systems.
- Compatibility with GPAW (parallelization, call structure).

Train a surrogate neural-network model

- Generate data (training, validation, test).
- Adapt the NN parameters and loss function.

Perform thorough evolutionary searches

- Utilize the CPU cluster and GPUs.
- Sets of CMA-ES runs with NN backend.



Covariance Matrix Adaptation Evolution Strategy (CMA-ES)


- Optimization technique based on ideas of evolution.
- Works for **rough energy landscapes**.
- Structures are sampled from a **multivariate normal distribution**.
- **Adaptation**: Repeat recent successful steps.

$$x_r^{(g+1)} \sim \mathcal{N}(m^{(g)}, (\sigma^{(g)})^2 C^{(g)})$$

Covariance Matrix Adaptation Evolution Strategy (CMA-ES)

- Optimization technique based on ideas of evolution.
- Works for **rough energy landscapes**.
- Structures are sampled from a **multivariate normal distribution**.
- **Adaptation**: Repeat recent successful steps.

$$x_r^{(g+1)} \sim \mathcal{N}(m^{(g)}, (\sigma^{(g)})^2 C^{(g)})$$




Hansen, N. (2016). arXiv:1604.00772 [cs.LG]

Covariance Matrix Adaptation Evolution Strategy (CMA-ES)

- Optimization technique based on ideas of evolution.
- Works for **rough energy landscapes**.
- Structures are sampled from a **multivariate normal distribution**.
- **Adaptation**: Repeat recent successful steps.

$$x_k^{(g+1)} \sim \mathcal{N}(m^{(g)}, (\sigma^{(g)})^2 C^{(g)})$$




Hansen, N. (2016). arXiv:1604.00772 [cs.LG]

Covariance Matrix Adaptation Evolution Strategy (CMA-ES)

- Optimization technique based on ideas of evolution.
- Works for **rough energy landscapes**.
- Structures are sampled from a **multivariate normal distribution**.
- **Adaptation**: Repeat recent successful steps.

$$x_k^{(g+1)} \sim \mathcal{N}(m^{(g)}, (\sigma^{(g)})^2 C^{(g)})$$




Hansen, N. (2016). arXiv:1604.00772 [cs.LG]

Covariance Matrix Adaptation Evolution Strategy (CMA-ES)

- Optimization technique based on ideas of evolution.
- Works for **rough energy landscapes**.
- Structures are sampled from a **multivariate normal distribution**.
- **Adaptation**: Repeat recent successful steps.

$$x_r^{(g+1)} \sim \mathcal{N}(m^{(g)}, (\sigma^{(g)})^2 C^{(g)})$$




Hansen, N. (2016). arXiv:1604.00772 [cs.LG]

Covariance Matrix Adaptation Evolution Strategy (CMA-ES)

- Optimization technique based on ideas of evolution.
- Works for **rough energy landscapes**.
- Structures are sampled from a **multivariate normal distribution**.
- **Adaptation**: Repeat recent successful steps.

$$x_r^{(g+1)} \sim \mathcal{N}(m^{(g)}, (\sigma^{(g)})^2 C^{(g)})$$




Hansen, N. (2016). arXiv:1604.00772 [cs.LG]

Covariance Matrix Adaptation Evolution Strategy (CMA-ES)

- Optimization technique based on ideas of evolution.
- Works for **rough energy landscapes**.
- Structures are sampled from a **multivariate normal distribution**.
- **Adaptation**: Repeat recent successful steps.

$$x_k^{(g+1)} \sim \mathcal{N}(m^{(g)}, (\sigma^{(g)})^2 C^{(g)})$$




Hansen, N. (2016). arXiv:1604.00772 [cs.LG]

Covariance Matrix Adaptation Evolution Strategy (CMA-ES)

- Optimization technique based on ideas of evolution.
- Works for **rough energy landscapes**.
- Structures are sampled from a **multivariate normal distribution**.
- **Adaptation**: Repeat recent successful steps.



$$x_r^{(g+1)} \sim \mathcal{N}(m^{(g)}, (\sigma^{(g)})^2 C^{(g)})$$




Hansen, N. (2016). arXiv:1604.00772 [cs.LG]

CMA-ES evolution on 4x1 structure

- 500 generations, 11000 individual structures.
- Subsequent local optimization.



Founder





Result

Neural-Network Force Field

Differentiable neural-network force field



- Trained on ab-initio **forces**.
- Atom-centered, **local descriptors**.
- **Transferable** to different system sizes.
- Built on Google JAX.



Training the NN potential

Fully trained model (4x1 structures)



- Weakly correlated structures.
- 3000 training data, 500 validation data.
- MAE $f = 75.3 \text{ meV}/\text{\AA}$



Training the NN potential

Fully trained model (4x1 structures)


- Weakly correlated structures.
- 3000 training data, 500 validation data.
- MAE $f = 75.3 \text{ meV/\AA}$
- MAE $E_{\text{pot}} = 2.2 \text{ meV/atom}$



Structure search

Investigate the 5x1 reconstruction



- Use the NN for energy evaluation.
- Run a set of 50 CMA calculations.
- Optimize each CMA result.
- Identified two distinct minima.



Structure search

Investigate the 5x1 reconstruction



- Use the NN for energy evaluation.
- Run a set of 50 CMA calculations.
- Optimize each CMA result.
- Identified two distinct minima.




NN performance on 5x1 structures

Test the 4x1 model

- 3500 test structures.
- Compare to GPAW results.



Workflow



Acknowledgements



TECHNISCHE
UNIVERSITÄT
WIEN



TACO
TAMING COMPLEXITY
TOGETHER





Der Wissenschaftsfonds.

Bonus - NN performance on 5x1 structures

Test the 4x1 model

- 3500 test structures.
- Compare to GPAW results.



Bonus - NN performance on 5x1 structures

Test the 4x1 model

- 3500 test structures.
- Compare to GPAW results.

